

Mode 2 series

Portable EV Charger Mini



Type 1

Type 2



Features

- Real mini** Easy hold by one hand
- High safety performance** Integrated main-board, high efficiency and eco-friendly
- Robust and durable** IP65 protection grade for outdoor use stably
- IP65** Safely use in some extreme environment
- Current adjustable** Max 5 levels charging current selection
- LED indicator** Status clearly indicated by different colours
- Multiple protection** All necessary protections are included

Optional wall end plug



MARON-ELECTRONICS
connected insights

Email : sales@maron-electronics.gr

Specification	
Model	TS-PEC-003
Electrical Properties	
Voltage	230VAC ±10%
Max Output Current	16A (6/8/10/13/16 Optional)
Frequency	50 / 60Hz
Max Output Power	3.5kw
Residual current protection	30mA as default 6mA is optional
Structure Design	
LED Indicator	5 Indicators
Charging Outlet	TYPE1/2 4.5M charging cable
Power incoming line	0.7M
Total cable length	>5M
Housing Material	PC+GF 10%
Front Panel	PC
Security Protection	
Safety Standard	IEC/EN 61000-6-1:2019; EN 61000-6-3:2007+A1; IEC 61000-6-1:2016; IEC 61000-6-3:2006+A1; CISPR 14-1:2016; IEC/EN 62752:2016+A1
Multiple Protection	Over/Under voltage protection, Surge protection,
Warranty	1 year
Environmental Performance	
Working temperature	-30 C ~+50
Working humidity	5%-95%, No condensation
Protection Level (control box)	IP65
Altitude	≤2000m
Application Site	Indoor/Outdoor
Cooling Method	Natural cooling
Packing Details	
Product Size	180*81*45mm